



US006278266B1

(10) Patent No.: US 6,278,266 B1
 (45) Date of Patent: Aug. 21, 2001

(54) SYMMETRICAL POWER GENERATOR AND
 METHOD OF USE

(76) Inventor: Martin S. Glasband, 5628 Lakeshore
 Dr., Selma, OR (US) 97538

(*) Notice: Subject to any disclaimer, the term of this
 patent is extended or adjusted under 35
 U.S.C. 154(b) by 0 days.

(21) Appl. No.: 09/568,217

(22) Filed: May 9, 2000

Related U.S. Application Data

(60) Continuation-in-part of application No. 08/848,123, filed on
 Apr. 28, 1997, now Pat. No. 6,060,876, which is a division
 of application No. 08/261,814, filed on Jun. 17, 1994, now
 Pat. No. 5,640,314.

(51) Int. Cl.⁷ H01F 17/00

(52) U.S. Cl. 323/355

(58) Field of Search 323/355, 359,
 323/247, 255, 258, 363/34, 36, 84, 125,
 171; 336/150, 192

(56) References Cited

U.S. PATENT DOCUMENTS

4,437,147 * 3/1984 Takamura et al. 363/61

4,584,637	*	4/1986	Takamura et al.	363/61
4,675,801	*	6/1987	Terada	363/143
5,140,705	*	8/1992	Kosuga	455/138
5,386,473	*	1/1995	Harrison	381/24
5,615,091	*	3/1997	Palatnik	363/17
5,900,764	*	5/1999	Imam et al.	327/343

OTHER PUBLICATIONS

Morrison, "Grounding and Shielding Techniques in Instrumentation"; Dynamics Instrumentation Company; John Wiley and Sons, Inc.; New York, London, Sydney; pp. 81-85, 1967.

* cited by examiner

Primary Examiner—Matthew Nguyen

(74) Attorney, Agent, or Firm—Larson & Taylor, PLC

(57) ABSTRACT

A power generator and method of use for providing symmetrical power. In the present invention, the output winding of a generator is center-tapped at the point of mean voltage differential between each of its two output terminals. The center-tap is grounded such that one-half of the output potential appears across each half of the output winding. Full, symmetrical voltage is applied to the load when the output terminals are connected to the load and the load is grounded.

4 Claims, 10 Drawing Sheets

